MANHATTAN
BRINGING COMPUTERS TO LIFE

Magnetic Strip Card Reader

PS/2, Triple Track Reader

Model
460897

Swipe with speed, accuracy and reliability.

MANHATTAN® Magnetic Strip Card Readers deliver high-quality data collection for a wide range of applications to help improve routine sales transactions and secured information exchanges. The standard-length slot reads high- and low-coercive strips and provides maximum stability and contact for accurate, bi-directional reads of up to three tracks of magnetic strip data. Tone and LED indicators confirm and signal valid data collection. Ideal for multiple uses, including retail point-of-sale and self-service transactions and access control applications, MANHATTAN Magnetic Strip Card Readers are easy to implement and simple to use. A built-in keyboard wedge decoder sends scanned data to an active application where it appears as if it were manually typed or directly keyed into the computer. Quick installation through any PS/2 port integrates with most PCs without an external power supply or complicated programming.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.

LIFETIME WARRANTY

LIFETIME WARRANTY

Model
460897

Features

- Helps speed data entry, reduce errors and improve efficiency – ideal for retail transactions, access control and ID verification correction reduces energy loss
- Keyboard Wedge Decoder displays data as if directly entered from keyboard
- Bi-directional swipe reads most bank cards, membership and ID badges, gift cards, driver's licenses and more
- Supports JIS II and decodes single-, dual- and triple-track data formats
- Switchable interface integrates with most PCs
- Easy to install and use without software or special training
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS
- FCC
- CE
- USB
- ISO 7810-7813
- JISII

GENERAL
- Read: high- and low-coercive strips
- Read direction: bi-directional swipe
- Reading indicator: tone and LED
- Scan rate: 100 – 1000 mm (3.9 – 39 in.) per second
- Interface: PS/2
- Supported interface: USB, PS/2, RS232, TTL (cables may be switched to different interfaces)

TRACK INFORMATION
- Single track (1, 2 or 3 tracks)
- Dual tracks (1 and 2, 2 and 3 tracks)
- Triple tracks (1 and 2 and 3 tracks)
- JIS II

PHYSICAL
- Dimensions: 150 x 43 x 43 mm (5.9 x 1.7 x 1.7 in.)
- Weight: 145 g (4.67 oz.)
- Cable length: 1.5 m (4.9 ft.)
- Operating temperature: 0 – 50°
- Storage temperature: -20 – 70°C
- Relative humidity: 20 – 95% (non-condensing)
- Housing: ABS and PC

ELECTRICAL
- Voltage: DC +5 V +/- 5%
- Power consumption: 130 mA

PACKAGE CONTENTS
- Magnetic Strip Card Reader
- Software CD (optional for setup)

For more information on MANHATTAN products, consult your local dealer or visit **www.manhattan-products.com**.

MANHATTAN
BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.